

Product Specifications

ACCULAB

sartorius group



=====
Balance meets requirements of Council
Directive 89/336/EEC (CE marking; EMC)
=====

Recommended accessories:

- Calibration weight with DKD*
certificate YCW6238-00
- Lock-down capability (for anti-theft
locking device) LC-1
- Data printer, adjustable for use in
legal metrology, with GLP/GMP
function YDP03-0CE

*DKD = German Calibration Service,
recognized throughout Europe
=====

ATL-2202

ACCULAB ATILON

Electronic precision balance with
backlit amber display segments and
symbols and choice of 4 filter levels
for optimal weighing results even under
adverse ambient conditions

=====
Weighing capacity 2200 g
Readability 0.01 g
Tare range (subtractive) 2200 g
Response time, typical 1.7 s
Repeatability <=± 0.01 g
Linearity <=± 0.02 g
=====
Weighing pan 180x180 mm
Balance housing (WxDxH) 215x305x97 mm
Net weight approx. 3.1 kg
=====

Standard features/equipment supplied:

- 25-contact bidirectional RS-232
data interface
- ISO/GLP-compliant data records
- Below-balance weighing port
- Overload protection
- Anti-theft locking device
- Leveling feet; level indicator near
display
- AC adapter
- Built-in application programs
(mass unit conversion, counting
with automatic reference sample
updating, weighing in percent, net-
total formulation, totalizing, animal
weighing, calculation by a factor
(division/multiplication)
- Calibration/adjustment at the press
of a key with external weight
- Built-in clock