

Product Specifications

ACCULAB

sartorius group



- Built-in clock

=====

Balance meets requirements of Council Directive 89/336/EEC (CE marking; EMC)

=====

Recommended accessories:

- Calibration weight with DKD* certificate YCW5138-00
- Lock-down capability (for anti-theft locking device) LC-1
- Data printer, adjustable for use in legal metrology, with GLP/GMP function YDP03-0CE

*DKD = German Calibration Service, recognized throughout Europe

=====

ATL-153

ACCULAB ATILON

Electronic precision balance with backlit amber display segments and symbols; choice of 4 filter levels for optimal weighing results under adverse ambient conditions.

=====

Weighing capacity	150 g
Readability	0.001 g
Tare range (subtractive)	150 g
Response time, typical	1.7 s
Repeatability	<=± 0.001 g
Linearity	<=± 0.002 g

=====

Weighing pan diameter	115 mm
Balance housing (WxDxH)	215x305x140 mm
Net weight	approx. 2.9 kg

=====

Standard features/equipment supplied:

- 25 contact bidirectional RS-232 data interface
- ISO/GLP-compliant data records
- Glass draft shield
- Below-balance weighing port
- Overload protection
- Anti-theft locking device
- Leveling feet; level indicator near display
- AC adapter
- Built-in application programs (mass unit conversion, counting with automatic reference sample updating, weighing in percent, net-total formulation, totalizing, animal weighing, calculation by a factor (division/multiplication))
- Calibration/adjustment at the press of a key with external weight