

# Product Specifications

# ACCULAB

sartorius group



- AC adapter
- Built-in application programs (mass unit conversion, counting with automatic reference sample updating, weighing in percent, net-totalizing, animal weighing, calculation by a factor (division/multiplication))
- Built-in clock
- Dust cover

=====

Balance meets requirements of Council Directive 89/336/EEC (CE marking; EMC)

=====

#### Recommended accessories:

- Calibration weight with DKD\* certificate YCW5128-00
- Lock-down capability (for anti-theft locking device) LC-1
- Data printer, adjustable for use in legal metrology, with GLP/GMP function YDP03-0CE

\*DKD = German Calibration Service, recognized throughout Europe

=====

## ATL-124

### ACCULAB ATILON

Electronic precision balance with backlit amber display segments and symbols and choice of 4 filter levels for optimal weighing results even under adverse ambient conditions.

=====

Weighing capacity	120 g
Readability	0.1 mg
Tare range (subtractive)	120 g
Response time, typical	2.5 s
Repeatability	<=± 0.1 mg
Linearity	<=± 0.2 mg

=====

Weighing pan diameter	90 mm
Weighing chamber (WxDxH)	170x170x212 mm
Balance housing (WxDxH)	215x305x305 mm
Net weight	approx. 4.2 kg

=====

#### Standard features/equipment supplied:

- 25-contact bidirectional RS-232 data interface
- ISO/GLP-compliant data records
- Glass draft shield
- Below-balance weighing port
- Overload protection
- Anti-theft locking device
- Leveling feet; level indicator near display