

Article Specification



- a Sartorius printer is connected to the balance
- Below-balance weighing equipment
 - Overload protection
 - Lug for attaching an antitheft locking device
 - Leveling feet, level indicator
 - AC adapter
 - Built-in application programs (mass unit conversion, counting with automatic reference sample updating, weighing in percent, net-total formulation, totalizing, animal weighing, calculation by a factor (division/multiplication))
 - Dust cover

=====

Optional accessories:

- External rechargeable battery set YRB05Z
- Printer YDP20-OCE
- Density determination kit YDK01LP

SARTORIUS M-Pact AX224

The balance for all standard applications in the laboratory. Simple, safe application due to automatic calibration at the touch of a button. Top quality weighing system. Backlit 14-segment display, 2 tare keys, stability indicator and 4 selectable filter levels plus optimized display update rate complete the picture: a balance for the professional.

=====

Weighing capacity	220 g
Readability	0.1 mg
Tare range (subtractive)	220 g
Measuring time - typical	3 s
Repeatability	<=± 0.2 mg
Linearity	<=± 0.2 mg

=====

Pan size (diameter)	90 mm
Weighing chamber (WxDxH)	185x182x230 mm
Balance housing (WxDxH)	230x310x305 mm
Net weight	approx. 4.8 kg

=====

Standard features/equipment supplied:

- Motorized calibration and adjustment function
- Bidirectional RS-232 data interface port
- ISO/GLP-compliant printing/recording of weighing and calibration data when