

# Centrifuges - compact general purpose

## Spectrafuge™ 6C

The *Spectrafuge 6C* has been designed for quick production of PPP (platelet poor plasma) or PRP (platelet rich plasma) as well as other applications in the clinical and research laboratory.

The removable rotor of the *Spectrafuge 6C* holds up to 6 x 15 mL conical tubes, and with adapters will accommodate most common blood draw tubes. The variable speed allows for a variety of applications to be performed. A timer controls operation from 30 seconds to 30 minutes or can be set to "hold" for continuous operation.

The control panel of the centrifuge features easy turn knobs and large digital displays for time and speed. During operation of the centrifuge, the lid is locked. Once the rotor has come to a stop, the lid knob can be pressed to unlock the lid and gain access to the samples.

A small footprint allows the *Spectrafuge 6C* to fit on even the most crowded bench. Its rugged construction will provide years of trouble free operation. The centrifuge can be operated on the bench or in a cold room.



CE

- Ideal for PPP and PRP production
- A Maximum speed 6,500 rpm/4,000 x g
- Digital control and accuracy
- Accepts 15 mL and most common blood draw tubes
- Small footprint
- Safe for cold room use

### SPECIFICATIONS

Speed range	300 rpm to 6,500 rpm
Maximum RCF	4,000 x g
Maximum capacity	6 x 10/15 mL
Timer	1 - 30 min or continuous
Dimensions (W x D x H)	8.25 x 7 x 9.5 in/21 x 18 x 24 cm
Weight	10 lb/4.5 kg
Electrical	120V or 230V~, 50/60 Hz

### ORDERING INFORMATION

Catalog No.

Description

C0060-230V\*

*Spectrafuge 6C* Centrifuge, complete with 6 x 10/15 mL rotor

C0200-17A

Adapter set for 5, 7 and 10 mL tubes, pack of 6

\*230V product includes both -EU and -UK power cords. For 120V units, remove -230V from end of catalog number.