

Fits in. Stands out.



Introducing the NEW! Thermo Scientific™ Sorvall™ ST 8 small benchtop centrifuge



Fits in.

- to **your space**, with its compact footprint.
- ▶ to your applications, accommodating multi-laboratory settings with the flexibility to adapt with evolving clinical and research needs.

CLINICAL APPLICATIONS

Clinical Chemistry

Clinical Microbiology

Hematology

Immunology

Clinical Studies

RESEARCH APPLICATIONS

Cellular Biology

Microbiology

Genomics / Molecular Biology

Proteomics

Biochemistry

Pharmaceutical Studies





Stands out.

- designed for solid reliability and consistent results.
- ▶ featuring innovative Thermo Scientific™ technologies:
- anticipating and addressing your most pressing lab needs. Even those you don't know you have yet.





Auto-Lock™ Rotor Exchange

Secure push-button application versatility and cleaning convenience



ClickSeal™ Biocontainment Lids

One-handed, certified¹ sample protection



Maximized Capacity

Process 8 x 50 mL conical tubes, 24 x 5/7 mL blood tubes, microplates and microtubes, all in one versatile unit

Biocontainment certification by the Public Health Laboratory Service, Microbiology

Fits in. Stands out.



Simple solutions. Flexible processing.

Secure, push-button **Auto-Lock** rotor exchange in less than 3 seconds delivers:

- Trouble-free rotor installation and removal
 - 1] No tools are required
 - 2 No complicated rotor changing procedures
- Clear chamber access for cleaning convenience
- Quick switch between applications from conical tubes to blood tubes, and from microtubes to microplates – and the flexibility to evolve with the changing needs of your laboratory

Optimize bench space with maximized capacity

- 8 x 50 mL swinging bucket rotor capacity or 4 microplates for research needs
- Clinical processing up to 24 x 5/7 mL blood tubes per run



Reliable quality. **Safe operation.**

- Biocontainment sealing options, including certified¹
 ClickSeal lids for glove-friendly, one-handed operation
- Manufactured with quality materials providing broad chemical resistance with exceptional strength for durability and reliability
- Quiet performance (<61 dBA) provides a safe, stress-free environment
- Conforms to the latest clinical and safety standards, such as UL, CE and IVD^{2, 3}



- Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK
- ² See full list of standards & certifications on final page
- ³ IVD compliant regarding directive 98/79/EC, if used together with the hematocrit rotor and its accessories



- One-touch operation with pre-saved protocols and password protection available
- Highly visible backlit display for easy reading of parameters across the lab
- Optional indicators at end of run, including automatic lid opening, flashing display or audible signal
- Glove- and detergent-friendly
- Multilingual instructions English, Dutch, French, German, Italian, Russian and Spanish — on programming, run conditions, alerts and service messages

4500 10:00

Fits in. clinical applications. Stands out.

Outstanding capacity in a compact design with a smart, simple interface.



Rotors for Clinical Applications

Thermo Scientific Rotor **Stand-out Features** Performance **Applications TX-150 Swinging Bucket Rotor** Clinical Chemistry Designed for a broad range of highspeed, high-capacity swing-out Certified1 sample 4,500 rpm Hematology processing needs, with a capacity of protection with ClickSeal 3,260 x g Immunology 24 x 5/7 mL blood tubes per run and biocontainment lids. flexibility with available adapters. Clinical Studies **M10 Swinging Bucket Rotor** Clinical Chemistry Transportable microplate 4,400 rpm Clinical Microbiology Centrifuge up to 4 microplates or carriers, complemented by 2 deepwell plates. 2,576 x g Hematology Auto-Lock rotor exchange. Immunology

CLINIConic Fixed Angle Rotor



Spin 30 blood tubes in fixed angle configuration with fast acceleration to optimize blood separation applications.

Auto-Lock rotor exchange for ultimate ease-of-use.

4,400 rpm 3,030 x g

- Clinical Chemistry Clinical Microbiology
- Hematology
- Immunology
- Clinical Studies

Hematocrit Rotor



Dedicated blood processing to achieve capillary separations.

Linear scale provided to read results.

13,300 rpm 16,800 x g

Hematology

1 😻 Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK

Dedicated Rotors for Routine Clinical Processing





TX-100S Clinical Swinging Bucket Rotor with Sealed Carriers

Spin 8 tubes with biocontainment sealing 4,500 rpm / 3,215 x g



TX-100 Clinical Swinging Bucket Rotor with Carriers

Capacity of 16 tubes per run 4,500 rpm / 3,260 x g

Fits in. research applications. Stands out.

Innovative design supports multiple users and applications to stay one step ahead of your evolving research needs.



Rotors for Research Applications **Thermo Scientific Rotor Description Stand-out Features** Performance **Applications TX-150 Swinging Bucket Rotor** Cellular Biology Designed for a broad range **Dedicated bucket available** Microbiology of swing-out processing for 8 conical tubes capacity 4,500 rpm Genomics/Molecular Biology needs at high speed and or round buckets with $3,260 \times g$ Proteomics high capacity with the certified1 ClickSeal Biochemistry flexibility of available adapters. biocontainment lids. Pharmaceutical studies **M10 Swinging Bucket Rotor** Centrifuge up to Transportable microplate Cellular Biology 4.400 rpm 4 microplates or carriers, complemented by Microbiology 2,576 x g 2 deepwell plates. Auto-Lock rotor exchange. Genomics/Molecular Biology MT-12 Swinging Bucket Rotor Unique design capable of Microbiology spinning up to 12 x 1.5/2 mL Individual swinging 13,000 rpm Genomics/Molecular Biology microtubes and filtration Biochemistry bucket rotors. 16,438 x g columns, ideal for small- Pharmaceutical Studies volume research applications. **HIGHConic III Fixed Angle Rotor** Cellular Biology New transparent lid Process 6 x 50 mL tubes in Microbiology enables veiwing for added Genomics/Molecular Biology fixed angle configuration 8,700 rpm safety and convenience, and and at RCF above 10,000 x q 10,155 x g Proteomics Auto-Lock rotor exchange in certified1 sealed conditions. Biochemistry enhances ease-of-use. Pharmaceutical Studies **CLINIConic Fixed Angle Rotor** Spin 30 x 15 mL round or Support conical tubes Cellular Biology conical tubes and ensure fast in a fixed angle rotor 4,400 rpm Microbiology acceleration and throughput with the flexbility of $3,030 \times g$ Genomics/Molecular Biology for cell culture applications. Auto-Lock rotor exchange. **Micro-Volume Rotors** 14,000 rpm MicroClick 30 x 2 **Fixed Angle Rotor** 21,693 x g Capable of supporting With Auto-Lock rotor micro-volume protocols, exchange, switch from Microbiology such as nucleic acid swing-out to a microtube MicroClick 24 x 2 16,000 rpm Genomics/Molecular Biology preparation, PCR reaction rotor in as little as 3 **Fixed Angle Rotor** 24,328 x g Biochemistry set-up and filtration columns, seconds, coupled with

8 x 8 PCR Strip

Fixed Angle Rotor

security of certified1 ClickSeal

15,000 rpm

17,860 x g

biocontainment lids.

choose from the complete

micro-volume rotor portfolio.

Pharmaceutical Studies

Stands out. Extensive Rotor Portfolio for Application Flexibility



Cat. No.	Description	Rotor Capacity (places x volume, mL)	Max Tube Dimensions (0 x L, mm)	Max Speed (rpm)	Max R((x g			
satile Swir	nging Bucket Rotors							
75005701	TX-150 Swinging Bucket Rotor, 90°, R _{max} 144 mm	4 x 145	50 x 100	4,500	3,26			
75005703	50 mL Conical Buckets (Unsealed, no adapter needed) (set of 4)	8 x 50	29.5 x 120	4,500	3,26			
75005702	Round Buckets (set of 4)	4 x 145	50 x 100	4,500	3,26			
75005707	ClickSeal Biocontainment Lids for Round Buckets (set of 4)							
75005724	Replacement O-rings for Lids (set of 4)							
Adapters for	Adapters for 50 mL Conical Buckets (sets of 2)							
75005808	15 mL Conical Tube	6 x 15	17 x 123					
Adapters for	Round Buckets (sets of 4)							
no adapter needed	145 mL Bottle (75005734)	4 x 145	50 x 100					
75005735	100 mL Round Bottom Open-Top Tube	4 x 100	45 x 117					
75005736	50 mL Conical or Skirted Tube	4 x 50	29.5 x 120					
75005744	25 mL Universal Flat/Skirted Tube	4 x 25	25 x 199					
75005737	15 mL Conical Tube	8 x 15	17 x 122					
75005737	11 mL IVF Tube	8 x 11	17 x 122					
75005737	14 mL Urine Tube	16 x 14	18 x 124					
75005738	12 mL Blood Collection Tube (Greiner®)	16 x 12	16 x 100					
75005738	10 mL Blood Collection or 15 mL Corex®/Kimble® Tube	16 x 15	17 x 117					
75005730	5/7mL mL Blood Collection Tube	24 x 5/7	13 x 116					
75005739	3/5 mL Blood Collection Tube	28 x 3/5	12 x 124					
75005740	1.5/2 mL Microtube	80 x 2	11 x 65					
		00 X Z	11 X 03					
Rotor Packa 75005760	Cell Culture Package, includes: TX-150 Rotor (75005701), Round Buckets	4 x 50	29.5 x 120					
75005761	(75005702), Adapters for 50 mL Conical Tubes (75005736) High Capacity Cell Culture Package , includes TX-150 Rotor (75005701), Capacity Publish (75005700), Adapter for 15 mt 15	8 x 50	29.5 x 120					
75005762	Conical Buckets (75005703), Adapters for 15 mL Conical Tubes (75005808) Clinical Rotor Package, includes: TX-150 Rotor (75005701), Round Buckets (75005702), ClickSeal Biocontainment Lids (75005707), Adapters for Blood Collection Tubes: 5/7 mL (75005739) and 10 mL (75005738)	24 x 5/7	18 x 124					
75005706	M10 Swinging Bucket Rotor, 90°, R _{max} 139 mm	4 Standard	n/a	4,400	2,57			
75005723	Unsealed Buckets (set of 2)	or 2 Deepwell		.,	_,			
75005600	MT-12 Swinging Bucket Rotor, 90°, R _{max} 87 mm	12 x 2	11 x 50	13,000	16,43			
nical Swing	ging Bucket Rotors							
75005704	TX-100S Clinical Swinging Bucket Rotor with Sealed Carriers, 90°, R _{max} 142 mm	8 x 15	17 x 106	4,500	3,21			
75005705	TX-100 Clinical Swinging Bucket Rotor with Carriers, 90°, R _{max} 144 mm	16 x 15	17 x 121	4,500	3,26			
Adapters for	TX-100S Clinical Rotor and TX-100 Clinical Rotor (each)							
11203666	13.5 mL Urine Tube	16/8 x 13.5	16 x 82					
11172596	5/7 mL BD Hemogard®/ BD Vacutainer® Tube	16/8 x 5/7	13 x 106					
11172595	5 mL BD Hemogard Tube	16/8 x 5	13 x 75					
11172287	3 mL Blood Collection Tube	16/8 x 3	11 x 70					

Fixed Angle Rotors



HIGHConic III Rotor



CLINIConic Rotor

MicroClick 24 x 2 Rotor



MicroClick 30 x 2 Rotor



8 x 8 PCR Strip Rotor

Hematocrit Rotor

	Cat. No.	Description	Rotor Capacity (places x volume, mL)	Max Tube Dimensions (0 x L, mm)	Max Speed (rpm)	Max RCI (x g)		
xed	Angle Rot	ors						
*	75005709	HIGHConic III Rotor, 45°, R _{max} 120 mm	6 x 50	38 x 105	8,700	10,155		
	75005731	Replacement Lid (each)						
	75003058	Replacement Sealing O-rings (set of 2 with grease)						
	Adapters for HIGHConic III Rotor (set of 6)							
	75005745	38 mL Round Bottom Tube	6 x 38	25.5 x 110				
	75005746	16 mL Round Bottom Tube	6 x 16	18 x 123				
	75005755	15 mL Conical Tube	6 x 15	17 x 123				
	75005747	12 mL Round Bottom Tube	6 x 12	16 x 95				
	75005748	6.5 mL Round Bottom Tube	6 x 6.5	13.5 x 114				
	75005749	3.5 mL Round Bottom Tube	12 x 3.5	11 x 100				
	75005750	1.5/2 mL Microtube	12 x 2	11 x 40				
	75003623	CLINIConic Rotor, 37°, R _{max} 140 mm	30 x 15	16.5 x 131	4,400	3,030		
	Adapters for CLINIConic Rotor (each)							
	no adapter needed	15 mL Round/Conical Bottom Tube	30 x 15	16.5 x 131				
	75003702	10 mL Round Bottom Tube	30 x 10	16.5 x 95				
	11172596	5/7 mL BD Hemogard/ BD Vacutainer Tube	30 x 5/7	13 x 106				
	11172595	5 mL BD Hemogard Tube	30 x 5	13 x 75				
*	75005719	MicroClick 30 x 2 Rotor, 45°, R _{max} 99 mm	30 x 1.5/2	11 x 45	14,000	21,693		
	75005730	Replacement ClickSeal Biocontainment Lid (each)						
	75005726	Replacement O-ring for Lid (each)						
*	75005715	MicroClick 24 x 2 Rotor, 45°, R _{max} 85 mm	24 x 1.5/2	11 x 45	16,000	24,328		
	75005725	Replacement ClickSeal Biocontainment Lid (each)						
	75003405	Replacement O-ring for Lid (each)						
	Adapters for MicroClick 30 x 2 Rotor and MicroClick 24 x 2 Rotor (sets of 30)							
	75005752	0.2 mL PCR Tube	30/24 x 0.25	6.5 x 20				
	75005753	0.5 mL Microtube	30/24 x 0.5	8 x 44				
	75005754	0.25 mL Microtube	30/24 x 0.25	6 x 46				
*	75005720	8 x 8 PCR Strip Rotor, 45°, R _{max} 71 mm	8 x 8 PCR strips	8 x 8	15,000	17,860		
	75005730	Replacement ClickSeal Biocontainment Lid (each)						
	75005726	Replacement O-ring for Lid (each)						
	75005733	Hematocrit Rotor, 45°, R _{max} 80 mm, includes Linear Scale	24 Capillaries	n/a	13,300	16,800		
	76000923	Capillaries (pack of 100)						
	75000964	Sealing Kit						
	76000938	Replacement Linear Scale Reading Graph						





Thermo Scientific Sorvall ST 8 Centrifuge

Specifications

Swing Bucket Rotors	
Max Capacity	4 x 145 mL (with TX-150 rotor)
Max Speed	4,500 rpm (with TX-150 rotor)
Min Speed	300 rpm (with TX-150 rotor)
Max RCF	3,260 x g (with TX-150 rotor)
Fixed Angle Rotors	
Max Capacity	6 x 50 mL (with HIGHConic III rotor)
Max Speed	16,000 rpm (with MicroClick 24 rotor)
Min Speed	300 rpm (with MicroClick 24 rotor)
Max RCF	24,328 x g (with MicroClick 24 rotor)

Control System	Microprocessor
Drive System	Direct, brushless induction drive
Rotor Locking System	Auto-Lock rotor exchange
Imbalance Detection System	SMARTSpin
Programs	4 protocols via direct access key, with naming option and password protection available
Pulse (Short) Run	Yes
Acceleration / Deceleration Rates	2 (standard and soft)
Centrifugation Chamber	Brushed stainless steel
Max Timer Range	9h, 99 min + continuous
Sound Level	<58 dBA (with TX-150 rotor); <61 dBA (with MicroClick 24 rotor)
Other Features	 Certified¹ ClickSeal biocontainment lids Multilingual selection: English, Dutch, French, German, Italian, Russian and Spanish
Max Power Consumption	310 W
Dimensions	
Height (lid open)	67 cm (26.8 in)
Height (lid closed)	31 cm (12.2 in)
Width	37 cm (14.6 in)
Depth	48 cm (18.9 in)
Weight	35 kg (77 lb)
Standards & Certifications	
Standards	IEC 61010-1, IEC 61010-2-020, IEC 61010-2-101, EN 61326-1
Certifications	UL Listed / CE marked / IVD compliant ³ / Certified ¹ biocontainment

Ordering Information

75007201	Sorvall ST 8 centrifuge, ventilated, 230 V, 50/60 Hz
75007200	Sorvall ST 8 centrifuge, ventilated, 120 V, 60 Hz
75007202	Sorvall ST 8 centrifuge, ventilated, 100 V, 50/60 Hz

Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK 3IVD compliant regarding directive 98/79/EC, if used together with the hematocrit rotor and its accessories The Project was defined for JQC, Regulation 862.2050 – Clinical Centrifuges

thermoscientific.com/smallbenchcentrifuge

© 2013 Thermo Fisher Scientific Inc. All rights reserved.

Greiner is a registered trademark of Greiner. Corex is a registered trademark of Corning Inc. Kimble is a registered trademark of Kimble Glass. BD Hemogard and BD Vacutainer are registered trademarks of BD Biosciences. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300 Austria +43 1 801 40 0 Belgium +32 53 73 42 41 China +800 810 5118 or +400 650 5118 France +33 2 2803 2180 Germany national toll free

Germany national toll free 0800 1 536 376 Germany international +49 6184 90 6000 India toll free 1800 22 8374 India +91 22 6716 2200 Italy +32 02 95059 552 Japan +81 3 5826 1616 Netherlands +31 76 579 55 55 New Zealand +64 9 980 6700 Nordic/Baltic/CIS countries +358 9 329 10200 Russia +7 812 703 42 15 Spain/Portugal +34 93 223 09 18 Switzerland +41 44 454 12 22 UK/Ireland +44 870 609 9203 USA/Canada +1 866 984 3766

Other Asian countries +852 2885 4613 **Countries not listed** +49 6184 90 6000

