

Model CB 60 | CO₂ incubators with hot air sterilization and heat sterilizable CO₂ sensor

BENEFITS

- Hot air sterilization at 180 °C, with sterilizable built-in CO₂ sensor minimizes the risk of contamination
- Homogeneous temperature distribution thanks to VENTAIR™ air jacket system
- Stable pH-values thanks to drift-free CO₂ IR sensor technology
- Saturated relative humidity up to 95 % RH
- Easy cleaning thanks to seamless, deep-drawn inner chamber



MAIN FEATURES

- Temperature range: room temperature plus 7 °C to 60 °C
- Humidity range: up to 95% RH
- Auto-sterilization with hot air at 180 °C
- Double-pan humidification system with condensation protection
- CO₂ gas-mixing jet with Venturi effect
- Hot-air sterilizable CO₂ sensor with infrared technology
- Display via color LCD monitor
- Lockable door handle
- Tightly-sealed inner door made of tempered safety glass
- Seamless, deep-drawn inner stainless steel chamber
- 2 perforated stainless steel shelves
- Units are stackable with stacking adapter
- Troubleshooting system with visual and audible alarms
- Computer interface: Ethernet
- Internal data recording and USB interface
- Zero-voltage alarm contact

ORDERING INFORMATION

Interior volume [L]	Voltage	Option model	Version	Art.-No.
Model CB 60				
53	200...240 V 1~ 50/60 Hz	Standard	CB060-230V	9040-0088
		with 4x divided inner door	CB060-230V-G	9040-0104
		with O ₂ control	CB060-230V-O	9040-0090
		with O ₂ control and with 4x divided inner door	CB060-230V-GO	9040-0106
	100...120 V 1~ 50/60 Hz	Standard	CB060UL-120V	9040-0089
		with 4x divided inner door	CB060UL-120V-G	9040-0105
		with O ₂ control	CB060UL-120V-O	9040-0091
		with O ₂ control and with 4x divided inner door	CB060UL-120V-GO	9040-0107

TECHNICAL DATA (Version 1-4 from 8)

Description	CB060-230V	CB060-230V-G	CB060-230V-O	CB060-230V-GO
Article Number	9040-0088	9040-0104	9040-0090	9040-0106
Performance Data Temperature				
Temperature range 7 °C above ambient temperature to [°C]	60	60	60	60
Temperature variation at 37 °C [± K]	0.3	0.3	0.3	0.3
Temperature fluctuation at 37 °C [± K]	0.1	0.1	0.1	0.1
Recovery time after 30 seconds door open at 5 Vol.-% CO ₂ [min]	5	5	5	5
Recovery time after 30 seconds door open at 5 Vol.-% O ₂ [min]			8	8
Recovery time after 30 seconds door open at 37 °C [min]	4	4	4	4
Performance Data Climate				
Humidity range [% RH]	90...95	90...95	90...95	90...95
Gas Data - CO₂-Data				
CO ₂ range [Vol.-% CO ₂]	0...20	0...20	0...20	0...20
CO ₂ measurement	IR	IR	IR	IR
Gas Data - O₂-Data				
O ₂ range [Vol.-% O ₂]	0...0	0	0.2...95	0.2...95
Electrical data				
Rated Voltage [V]	200...240	200...240	200...240	200...240
Power frequency [Hz]	50/60	50/60	50/60	50/60
Nominal power [kW]	1	1	1	1
Unit fuse [A]	10	10	10	10
Phase (Nominal voltage)	1~	1~	1~	1~
Measures - Outer dimensions				
Width net [mm]	580	580	580	580
Height net [mm]	720	720	720	720
Depth net [mm]	545	545	545	545
Wall clearance back [mm]	100	100	100	100
Wall clearance sidewise [mm]	50	50	50	50
Measures - Doors				
Inner doors	1	4	1	4
Unit doors	1	1	1	1
Measures - Internal Dimensions				
Width [mm]	400	400	400	400
Height [mm]	400	400	400	400
Depth [mm]	330	330	330	330
Measures				
Interior volume [L]	53	53	53	53
Net weight of the unit (empty) [kg]	60	65	63	68
permitted load [kg]	30	30	30	30
Load per rack [kg]	10	10	10	10
Environment-specific data				
Energy consumption at 37 °C	80 Wh/h	80 Wh/h	80 Wh/h	80 Wh/h
Fixtures				
Number of shelves (standard/maximum)	2/3	2/2	2/3	2/2

TECHNICAL DATA (Version 5-8 from 8)

Description	CB060UL-120V	CB060UL-120V-G	CB060UL-120V-O	CB060UL-120V-GO
Article Number	9040-0089	9040-0105	9040-0091	9040-0107
Performance Data Temperature				
Temperature range 7 °C above ambient temperature to [°C]	60	60	60	60
Temperature variation at 37 °C [± K]	0.3	0.3	0.3	0.3
Temperature fluctuation at 37 °C [± K]	0.1	0.1	0.1	0.1
Recovery time after 30 seconds door open at 5 Vol.-% CO ₂ [min]	5	5	5	5
Recovery time after 30 seconds door open at 5 Vol.-% O ₂ [min]			8	8
Recovery time after 30 seconds door open at 37 °C [min]	4	4	4	4
Performance Data Climate				
Humidity range [% RH]	90...95	90...95	90...95	90...95
Gas Data - CO₂-Data				
CO ₂ range [Vol.-% CO ₂]	0...20	0...20	0...20	0...20
CO ₂ measurement	IR	IR	IR	IR
Gas Data - O₂-Data				
O ₂ range [Vol.-% O ₂]	0	0	0.2...95	0.2...95
Electrical data				
Rated Voltage [V]	100...120	100...120	100...120	100...120
Power frequency [Hz]	50/60	50/60	50/60	50/60
Nominal power [kW]	1	1	1	1
Unit fuse [A]	16	16	16	16
Phase (Nominal voltage)	1~	1~	1~	1~
Measures - Outer dimensions				
Width net [mm]	580	580	580	580
Height net [mm]	720	720	720	720
Depth net [mm]	545	545	545	545
Wall clearance back [mm]	100	100	100	100
Wall clearance sidewise [mm]	50	50	50	50
Measures - Doors				
Inner doors	1	4	1	4
Unit doors	1	1	1	1
Measures - Internal Dimensions				
Width [mm]	400	400	400	400
Height [mm]	400	400	400	400
Depth [mm]	330	330	330	330
Measures				
Interior volume [L]	53	53	53	53
Net weight of the unit (empty) [kg]	60	65	63	68
permitted load [kg]	30	30	30	30
Load per rack [kg]	10	10	10	10
Environment-specific data				
Energy consumption at 37 °C	80 Wh/h	80 Wh/h	80 Wh/h	80 Wh/h
Fixtures				
Number of shelves (standard/maximum)	2/3	2/2	2/3	2/2

OPTIONS AND ACCESSORIES

Designation	Description	*	Art.-No.
Access port with silicone plug	30 mm, back	01	8012-0558
	30 mm, left	01	8012-0559
	30 mm, right	01	8012-0560
Analog output, 4 – 20 mA	for temperature and CO ₂ values (outputs not adjustable)	–	8012-0822
Base	with casters	–	9051-0031
Calibration certificate O ₂	for the O ₂ control option; a measuring point in center of chamber at a specified O ₂ percentage value	–	8012-0229
Calibration certificate, expanded	for temperature; for extending the measurement in center of chamber to include another test temperature	–	8012-0022
Calibration certificate, temperature	for temperature, measurement in center of chamber at specified temperature	–	8012-0030
	temperature measurement incl. certificate and 27 measuring points at specified temperature	–	8012-0921
	temperature measurement incl. certificate, 15- 18 measuring points at specified temperature	–	8012-0918
	temperature measurement incl. certificate, 9 measuring points at specified temperature	–	8012-0915
Calibration certificate, temperature and CO ₂	for temperature and CO ₂ , temperature measurement in center of chamber, CO ₂ measurement performed using test gas at 37 °C and 5 % CO ₂	–	8012-0228
Electric access port	8-pin, for low voltage with LEMO socket (coverable) and LEMO plug (max. 24 V – 2 A)	–	8012-0826
Gas cylinder connection set	for CO ₂ , consisting of a gas tank pressure regulator with connection parts and 5-meter hose	–	8012-0014
	for N ₂ , consisting of a gas tank pressure regulator with connection parts and 5-meter hose	–	8012-0016
	for O ₂ , consisting of a gas tank pressure regulator with connection parts and 5-meter hose	–	8012-0015
Gas tank changer	external, BINDER Gas Supply Service, for connecting 2 gas tanks (CO ₂ , N ₂ or O ₂), with audible and visual alarms, as well as zero-voltage alarm output	–	8012-0408
Interface converter	RS 422 cable set and RS 232 / RS 422 interface converter for connection to 10-way plug distributor or for connection to a unit		
	120 V, 60 Hz option model	–	8012-0557
	230 V, 50/60 Hz option model	–	8012-0556
	RS 422 cable set and RS 422 / Ethernet interface converter for connection to 10-way plug distributor or for connection to a unit		
Interface converter, USB / RS422	120 V, 60 Hz option model	–	8012-0405
	230 V, 50/60 Hz option model	–	8012-0380
Interface converter, USB / RS422	RS 422 cable set and RS 422 / USB interface converter for connection to 10-way plug distributor or for connection to a unit (USB-powered converter)	–	8012-0665
Interior socket	waterproof, switched flush-mounting box (LEMO) for nominal voltage in unit interior, coverable, with corresponding plug (nominal voltage; max. 3 A; protection class IP65)	07	8012-0823
Magnetic Pouch (A4)	insert pouch with magnetic strip	–	1007-0065
pH-neutral detergent	concentrated, for gentle remove of residual contaminants; 1 kg	–	1002-0016
RS 422 interface	in place of Ethernet, for communication software	–	8012-0824
	modular plug distributor for 10 RS 422 interfaces	–	8012-0295
RS 422 interface, cable (15 m)	RS 422 connection cable (15 m) between plug distributor and RS 422 interface	–	5023-0036
RS 422 interface, cable (50 m)	RS 422 extension cable (50 m) between interface converter and unit or RS 232 / RS 422 plug distributor	–	5023-0117
Shelf, perforated	stainless steel	–	6004-0136
	stainless steel, for divided inner door	–	6004-0140
Software	APT-COM™ communications software		
	version 2 to 3, GLP edition	19	9053-0016
	version 3, BASIC edition	19	9053-0014
	version 3, GLP edition	19	9053-0015
	version 3, STANDARD edition	19	9053-0013
Stacking adapter, flat	APT-COM™ communications software, price: for free		
	version 3, GLP DEMO Edition	19	9053-0008
Stacking adapter, flat	for thermally decoupled stacking of two identical units	–	9051-0037

* Notes > See last page

SERVICES

Designation	Description	*	Art.-No.
Installation services			
Installation	and set up of unit at operating location, connect to existing connections	13, 18	DL100200
Instruction	unit function instructions for operation and programming of the controller	18	DL100500
Preventive maintenance			
Preventive maintenance	Execution of equipment inspection according to maintenance plan	14, 18	DL200400
Calibration services			
Calibration CO ₂	including certificate, CO ₂ measurement with analyzed test gas at 5 % or at specified value	14, 16, 17, 18	DL300401
Calibration O ₂	calibration of O ₂ , including certificate (one measuring point in center of chamber at specified O ₂ percentage)	14, 16, 17, 18	DL300402
Calibration temperature	including certificate, one measuring point in center of chamber at specified temperature	14, 16, 17, 18	DL300101
Temperature measurement 18 measuring points	including certificate, 18 measuring points at specified temperature	14, 16, 17, 18	DL300118
Temperature measurement 27 measuring points	including certificate, 27 measuring points at specified temperature	14, 16, 17, 18	DL300127
Temperature measurement 9 measuring points	including certificate, 9 measuring points at specified temperature	14, 16, 17, 18	DL300109
Validation services			
Execution of IQ/OQ	in accordance with qualification folder	15, 18, 20	DL410200
Execution of IQ/OQ/PQ	in accordance with customer's requirement, price: on request	15, 18	DL440500
Qualification folder IQ/OQ	supporting documents for validation performed by customer, consisting of: IQ/OQ checklists, unit schematics, QM certificate in accordance with ISO 9001	15, 18, 20	8012-0876
Qualification folder IQ/OQ/PQ	supporting documents for validation performed by customer, in accordance with customer's requirement, extension of Qualification folder IQ/OQ by chapter PQ	15, 18	8012-0963
Warranty service			
Extension of the warranty from 2 to 3 years	beginning with the date of delivery, wearing parts are not included	-	DL021041
Extension of the warranty from 2 to 5 years	beginning with the date of delivery, wearing parts are not included	-	DL021042

* Notes › See last page

NOTES

- 01 Condensation may occur in the area around the access port. Access ports may be placed in custom locations for an additional charge.
- 02 UL mark is not granted when this option is used.
- 03 Heat resistant only to max. 200 °C.
- 04 Only available on units rated for 230 V.
- 06 Heating-up time may increase as a result of the lower heat conductivity.
- 07 The additional heat input may affect the temperature behavior.
- 09 Not in conjunction with the optional access port, door with window and interior lighting.
- 10 Not available on 23-liter units.
- 11 Not available on 23- or 53-liter units.
- 12 Only available on units rated for 230 V or 400 V.
- 13 Installation and connections take place at unit location; transport within the company only upon consultation.
- 14 We recommend a BINDER service contract (see the chapter on BINDER Service) to cover unit inspections, calibrations and validations.
- 15 OQ according to Yellow Paper = completed factory validation documentation of all OQ checklists.
- 16 Sensor calibration is performed in an accredited calibration laboratory.
- 17 Calibration is performed according to the BINDER factory standard.
- 18 Quoted prices do not include travel costs. Please refer to the chapter on BINDER Service for travel costs for your region. Quoted prices for services performed in Switzerland do not include a country-specific added fee (available on request).
- 19 For additional accessories, refer to the Process documentation chapter.
- 20 When ordering IQ/OQ qualification folders and associated IQ/OQ execution on one order, we offer a 15 % discount for both items.
When ordering IQ/OQ/PQ qualification folders and associated IQ/OQ/PQ execution on one order, we offer a 15 % discount for the item of the IQ/OQ/PQ folder.

BINDER GmbH
Tuttlingen, Germany
TEL +49 7462 2005 0
FAX +49 7462 2005 100
info@binder-world.com
www.binder-world.com

BINDER Asia Pacific (Hong Kong) Ltd.
Kowloon, Hong Kong, P.R. China
TEL +852 39070500
FAX +852 39070507
asia@binder-world.com
www.binder-world.com

Representative Office for CIS
Moscow, Russia
TEL +7 495 988 15 16
FAX +7 495 988 15 17
russia@binder-world.com
www.binder-world.ru

BINDER Environmental Testing
Equipment (Shanghai) Co., Ltd.
Shangha, P.R. China
TEL +86 21 685 808 25
FAX +86 21 685 808 29
china@binder-world.com
www.binder-world.com

BINDER Inc.
Bohemia, NY, USA
TEL +1 631 224 4340
FAX +1 631 224 4354
usa@binder-world.com
www.binder-world.us