

CENTRIFUGES

SW 12



4x750 ml
Ventilated
Refrigerated

DJB Labcare - The UK's Leading Centrifuge Specialist
info@djblabcare.co.uk www.djblabcare.co.uk
01908 612598



SECURITY, EFFICIENCY, SAFETY

Firlabo have a long history of designing and manufacturing centrifuges.

This ability allows them to maintain a wide range of models which meet the needs of many customers.

SW12 centrifuges can spin tubes from 0.2 to 750 ml which makes them suitable for clinical, biological and research applications as well as for industrial uses.



SW12 centrifuges will accept most of the commonly available tubes and microplates. The range has been designed to be easy to operate and programme and to simplify servicing and functional testing.

As an overview, the range includes ventilated, refrigerated and thermostatically controlled models.

They can bench mounted, or mounted on trolley with castors.

The versatile controlsystem gives the operator many options and provides access to useful technical data held in the memory.

The brushless, induction motor greatly reduces servicing intervals.

SW12 centrifuges can repeat specific programmes to ensure reproducible results.



SECURITY : Sealed carriers as standard, lid locks, imbalance detection, powerfull induction motor.

Efficiency : Parameters are display alphanumericly, a buzzer sounds at the end of each cycle, speed displayed in g or rpm, 9 code-protected programmable cycles and one fast cycle, controlled acceleration and deceleration rates to protect your cells, the lid has assisted closing and a safety lock.

Safety : For optimum safety whilst in use, the **SW12** range is extremely robustly constructed and is designed for reliability.

DJB Labcare - The UK's Leading Centrifuge Specialist
info@djb-labcare.co.uk www.djb-labcare.co.uk 01909 612598

POLYVALENCE OF DESIGN AND USE



SW12R and SW12RH

The internal cooling system operates quietly to maintain +4°C at 4500 rpm when long cycles are used. To protect environment, only **CFC** and **HCFC** – free refrigerant gazes are used.

SW12 and SW12H

The non-refrigerated models are quiet and easy to use. The H (high) models are mounted on a trolley with castors. They are easy to move and save laboratory space.



SW12



SW12 R



SW12 H and RH

SPECIFICATION

Maximum speed with carriers (rpm)	4500			
Maximum speed with angular rotor (rpm)	7700			
Maximum acceleration with carriers (g)	4200			
Maximum acceleration with angular rotor (g)	9200			
Maximum capacity with carriers (ml)	4 x 750			
Maximum capacity with angular rotor (ml)	8 x 100			
Type of motor	Induction motor without brushes			
Microprocessor controller	as standard			
Acceleration	9 programmable ramps			
Braking	9 programmable ramps			
Program storage	10 programs in memory			
Radius	Standard			
Integrated maintenance	Standard			
Sealed carriers	Standard			
	SW12	SW12H	SW12R	SW12RH
Gross weight (kg)	78	97	119	131
Net weight (kg)	68	85	105	119
Dimensions HxWxD (mm)	425x520x635	425x520x635	425x750x635	995x520x635
Input power maximum (W)	900	900	1700	1700
Temperature range	From - 10°C up to + 40°C			
Temperature performance at 4500 rpm	+ 4°C			

DJB Labcare - The UK's Leading Centrifuge Specialist
 info@djblabcare.co.uk www.djblabcare.co.uk 01908 612598



EASE OF USE

The **SW9** has an assisted closing system which makes opening and closing the lid very easy. Just lower the cover and the centrifuge will close and lock by itself. At the end of the cycle, press "open" and the cover will open automatically.

EQUIPMENT

Type	Reference	Capacity	∅ (mm)	Tube height	Maxi radius (mm)	Maxi speed (rpm)	Maxi acceleration (g)
4 place swing out	FA3CENSW12001	4x750 ml			180	4500	3850
4 sealed carriers	FA3CENSW12002	4x750 ml	97		180	4500	3870
4 adapters	FA3CENSW12010	4x44 0.8 ml tubes	8.5	40	170	4500	3960
4 adapters	FA3CENSW12011	4x30 1.5 ml tubes	11.6	40	171	4500	3870
4 adapters	FA3CENSW12012	4x30 4.5 ml tubes flat bottom	11.6	58	175	4500	3870
4 adapters	FA3CENSW12013	4x30 5 ml tubes	13.5	58	171	4500	3870
4 adapters	FA3CENSW12014	4x30 6 ml tubes Vacutainer	13.5	100	171	4500	3940
4 adapters	FA3CENSW12015	4x30 6 ml tubes	13.5	108	171	4500	4140
4 adapters	FA3CENSW12016	4x30 6 ml tubes hemogard	14	108	171	4500	4140
4 adapters	FA3CENSW12017	4x19 10 ml tubes vacutainer	16.5	105	174	4500	3960
4 adapters	FA3CENSW12018	4x9 15 ml tubes falcon corning	17.5	125	183	4500	4140
4 adapters	FA3CENSW12019	4x7 15 ml tubes Vacutainer	18	130	175	4500	3870
4 adapters	FA3CENSW12020	4x7 15 ml tubes starsted	17	130	175	4500	3870
4 adapters	FA3CENSW12021	4x12 20 ml tubes	22.2	105	183	4500	4140
4 adapters	FA3CENSW12022	4x4 50 ml tubes falcon	30	120	171	4500	3940
4 adapters	FA3CENSW12023	4x4 50 ml tubes	33	115	183	4500	4100
4 adapters	FA3CENSW12024	4x2 100 ml tubes	44	115	174	4500	4140
4 adapters	FA3CENSW12025	4x1 225 ml tubes conique	65	135	181	4500	4030
4 adapters	FA3CENSW12026	4x1 250 ml tubes	65	135	183	4500	4030
4 adapters	FA3CENSW12027	4x1 450 ml tubes	82	125	178	4500	4030
4 Microtitre plate carrier	FA3CENSW12030	Rubber pads for 750 ml tubes	97				
Angular rotor	FA3CENSW12003	4x4 standard plates of 96 wells			156	3000	
Angular rotor	FA3CENSW12004	8 holes	44	115	140	7500	8820
Angular rotor	FA3CENSW12005	10 holes	35	115	145	7700	9120
Angular rotor	FA3CENSW12006	20 holes	18.6	115	145	7500	9020

Adapters for special tubes please ask us



8 Boulevard Monge - 69330 MEYZIEU (France)
 Tel : 00 33 4 78 04 75 75 - Fax : 00 33 4 78 04 75 76
 e-mail : firlabo@imagnet.fr www.firlabo.fr

DJB Labcare - The UK's Leading Centrifuge Specialist
www.djblabcare.co.uk 01908 612595
 info@djblabcare.co.uk

Your distributor :