The Thermo Scientific Heraeus Labofuge 300 is a small medical centrifuge with swinging bucket rotor, ideal for centrifugation of blood collection tubes and medical laboratories or practices with low sample throughput.

Thermo Scientific Heraeus Labofuge 300


An economical and comprehensive small medical centrifuge with swinging bucket rotor

Benefits

- Economical small centrifuge with swinging bucket rotor
- Ideal centrifugation of blood collection tubes
 Complete system with 8-place swinging
- bucket rotor and buckets
- Outstanding quality and reliability with induction drive and microprocessor control



Swinging Bucket Rotor



Blood Collection Tubes with Gel Barrier

- **A.** Using fixed angle rotors with gel barrier blood collection tubes can result in plasma contamination.
- **B.** The swinging bucket rotor purifies plasma with no red blood cell contamination.



Ideal for Virus Testing

The Thermo Scientific Heraeus Labofuge 300 is particularly suited to diagnostics and therapy of viral diseases (HIV, hepatitis).

In the field of virus testing, tubes with a gel barrier ("gel tubes") are commonly used. Immediately after a blood sample has been taken, these tubes must be spun.

Once centrifugation is complete, the blood plasma is separated from red blood cells by a layer of gel. This gel layer prevents making ing and resultant decomposition of viruses. Unlike fixed angle rotors, which can least to contamination within the per ube, the Heraeus® Labofuge® 300s swinging bucket rotor ensures the generative sucks to the tube wall with no traces of contamination in the plasma. The tubes can then be stored or transported to a laboratory for virus testing.

> Heraeus Labotuge 300 can also spin Iar Slood sample tubes and glass tubes.



Thermo Scientific Heraeus Labofuge 300 Centrifuge

Specifications			
Drive		Induction drive without carbon brushes	
Control		Microprocessor control through Easycontrol I with variable pre-selection an	
		display of speed and time, Quick-run	
Max. speed	rpm	4000, adjustable in increments of 10	
Min. speed	rpm	300	
Max. RCF	x g	2028	
Temperature range	°C	-	
Noise level at max. speed	dB	< 60	
Run time	min	0–99, cont. operation	
Program memory		The most recent data remains in the memory	
Construction		Galvanized steel chassis with armored chamber and plastic outer casing	
Centrifuge protection		Lid lock and interlock	
Dimensions (H x W x D)	mm (inch)	315 x 380 x 475 (12.4 x 15 x 18.7)	
Weight	kg (lb)	30 (66)	
Power consumption	W	180	
Test standards		Manufactured and tested in accordance with EN 61 010-1,	
		EN 61 010-2-020, EN 50 081-1,	
		EN 50 082-1; UVV VBG 7z test is not required, CE, CSA (120V only)	

Rotor Specifications		Swinging Bucket	35° Fixed Angle	
Cat. No		76003265*+	75003760 ⁺	
Max. speed	rpm	3600	4000	
Max. RCF	x g	2028	1915	
Max. capacity	mL	8 x 15	12 x 15	
Braking/accel. curves	sec	28/29	30/32	
Min./max. radius	mm (inch)	57/140 (2.2/5.5)	51/107 (2.0/4.2)	

* Included with Labofuge 300 ⁺Complete with all adapters necessary

Accessories

	Max. tube size	Tubes	Color	Cat No.			
	diam. x length mm (inch)	per rotor	buckets				
Accessories 76003265:							
15 mL bucket	16.5 (0.7) x 113 (4.5)	8	red	76003262			
7 mL bucket	13 (0.5) x 113 (4.5)	8	yellow	76003263			
5 mL pad	NA x 90 (3.5)	-	-	76003266			
Accessories 75003760:							
5 mL adapter	13 (0.5) x 75 (2.95)	12	tan	76003226			
7 mL adapter	13 (0.5) x 113 (4.5)	12	yellow	76003225			
10 mL pad	16.5 (0.7) x 117 (4.6)	6	-	75003762			
Protective sleeves for glass	16 (0.6) x 100 (3.9)	12	-	75003763			
5							

Ordering Information

Description

Heraeus Labofuge 300 with 8 x 15 mL swinging bucket rotor 8 buckets each for 7 mL and 15 mL and distance pads, 120V / 60Hz Heraeus Labofuge 300 with 8 x 15 mL swinging bucket rotor 8 buckets each for 7 mL and 15 mL and distance pads, 230V / 50-60Hz

© 2008 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms a ing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.



www.thermo.com/centrifuge

North America: USA/Canada +1 866 984 3766

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2000, Germany national toll free 08001-536 376. Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254, Netherlands +31 76 571 4440, Nordic countries +356 329 1(C) Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203 Asia: China +86 21 6865 4588 or +86 10 8419 3588, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian controls +852 365 4613 Countries not listed: +49 6184 90 6940 or +33 2 2803 2000



Cat. No.

75003231

DS-LECF-LAB0300-1108